

Cleanfloc CP Series

Powdery, cationic flocculants

Product description:

The Cleanfloc CP series contains powdered, cationic flocculants with an cation activity between 0 - 100%.

Due to the large number of molecular weight variants, the Cleanfloc CP series is very versatile for various applications and offers the finest combination of cationic activity and molecular weight, always the optimum combination for your application.

The Cleanfloc AP series is highly concentrated and promises 100% active substance, taking into account the specified maturation time.

Physical properties:

Bulk density:	1.1 ± 0.15 g/cm ³
pH-Value:	5.5 ± 1.5 @ 5g/l
Brookf. Viscosity:	500 cps @ 5g/l
Solubility in water:	unlimited

The Cleanfloc CP series is suitable by its cationic character for the flocculation of organic sludges for example in municipal waste water plants.

Dosage:

The dosage depends on many factors such as the concentration of particles to be flocculated and some interfering factors, e.g. Surfactants. In any case, it is advisable to carry out laboratory and operational tests and to determine the required dosing quantity. Usual dosage amounts are generally between 5 and 50 l/m³.

Application-Guide:

Galvanizing plants:	+	Biogas plants:	++++
Electro polishing:	-	Recycling companies:	++++
Automotive industry:	++	Tank cleaning facilities:	+++
Incineration plants:	-	Industrial purposes:	-
Coal power plants:	+	Leather industry:	+++
Soil remediation:	+++	Paper industry:	++++
Circuit board industry:	-	Food industry:	+++
Municipal waste water:	++++	Paint shops:	+++
Stone factories:	-	Oil processing:	++++
Concrete factories:	-	Textile industry:	+++

At a glance:

pH application area:	pH 2 - 11
Temp. Application area:	5 – 80°C
Matuation time:	40 - 60 minutes
Reaction time:	5 – 25 minutes
Highly recommended for:	Municipal waste water; Biogas plants; Recycling companies; Paper industry; Oil processing;
Storage conditions:	0 – 35°C

